

**VIN Deciphering Information for Advanced Metal Fabrication and Machine Inc.
Doing Business As "Tow Sport"**

VIN Deciphering		
1 st Section		
Position 1	WMI	1 - Assigned by SAE
Position 2	WMI	A - Assigned by SAE
Position 3	WMI	9 - Assigned by SAE
2 nd Section		
Position 4	Make	A = Advanced Metal Fabrication and Machine, Inc. T = Tow Sport
Position 5	Type of Trailer	1 = Ball Type Pull 2 = Pintle Hitch 3 = Gooseneck 4 = Straight Semi 5 = Fifth Wheel 6 = Kingpin
Position 6	Body Type	1 = Enclosed box trailer which has a open top storage area on top of the main box 2 = Fully enclosed trailer
Position 7	Length	In order to provide the most consistent and verifiable length representation length is measured from one extremity to the other. Trailers with adjustable tongues are measured with the tongue set to the shortest towable position. Easily removable, non-standard, or optional components that do not impact the ability to tow the trailer, or those installed but the dealer or customer such as an optional spare tire mount, are excluded from the length. A = less than 4 feet B = 4 feet to less than 6 feet C = 6 feet to less than 8 feet D = 8 feet to less than 10 feet E = 10 feet to less than 12 feet F = 12 feet to less than 14 feet G = 14 feet to less than 16 feet H = 16 feet to less than 18 feet J = 18 feet to less than 20 feet
Position 8	Axle Configuration	1=1 axle 2=2 axles 3=3 axles
3 rd Section		
Position 9	Check Digit	Calculated see 49 CFR 565.15(c)

**VIN Deciphering Information for Advanced Metal Fabrication and Machine Inc.
Doing Business As "Tow Sport"**

4 th Section		
Position 10	Model Year	F = 2015 G = 2016 H = 2017 J = 2018 K = 2019 L = 2020 M = 2021 N = 2022 P = 2023 R = 2024 S = 2025 T = 2026 V = 2027 W = 2028 X = 2029 Y = 2030 1 = 2031 2 = 2032 3 = 2033 4 = 2034 5 = 2035 6 = 2036 7 = 2037 8 = 2038 9 = 2039
Position 11	Plant of Manufacture	P = Prescott, AZ
Position 12	WMI	9 - Assigned by SAE
Position 13	WMI	9 - Assigned by SAE
Position 14	WMI	4 - Assigned by SAE
Position 15	Sequentially Assigned	
Position 16		
Position 17		